

# FIRE EAGLE®

Art. No.: 507501

## CE 0197 EN 15090:2012 HI3 CI M SRC - type F2A

Leather thickness 2.0 – 2.2 mm, waterproof, breathable, with CROSSTECH® laminate technology preventing bacteria and virus ingress, shaft height 23 cm, anti-static, XP017 sole

Available in sizes UK 3 – 12, extra sizes: UK 12 ½ – 15



HAIX® Fast Lacing Fit System



HAIX® Climate System



HAIX® High Durability Cap System



HAIX® Vario Wide Fit System



Boot jack



507501

### Uppers

Waterproof leather, hydrophobised, breathable (5.0 mg/cm<sup>2</sup>/h), thickness 2.0 – 2.2 mm

### Inner lining

Consisting of 3 layers in CROSSTECH® laminate technology, waterproof and breathable. Abrasion-proof lining fabric for optimised climate comfort at all times of the year, and especially when frequently moving between indoors and outdoors. Excellent penetration protection against blood and other bodily fluids (thus preventing ingress of viruses and bacteria). Enhanced protection against chemicals.

### Insert

Moisture wicking comfort insert with cushioning effect and antibacterial properties. Separate heel cup ensures optimized cushioning and foot guidance. „AIRFLOW“ channels. „Perfect-Fit“ marking for optimized boot size choice.

### Insole

Moisture-absorbent fleece insole.

### HAIX® High Durability Cap System

TPU cap with special profile for longer service life.

### HAIX® Composite Toe Cap

Anatomically shaped, ultra-light toe cap made from fibre-reinforced synthetic, conforming to the highest safety standards.

### Puncture resistant sole

Flexible, lightweight metal sole insert preventing punctures (patent pending).

### Sole

Lightweight rubber/PU sole in a sports style with sturdy road/rough terrain profile and enhanced toe-to-heel support; wear-resistant with excellent anti-slip properties - even in cold weather. The lightweight PU shock absorption wedge provides extra walking comfort and excellent thermal insulation. The flame-resistant outer sole is non-marking according to EN 15090:2012 and offers excellent resistance against heat, oil and fuels. Its bright yellow signal marks are visible even through thick smoke.

### HAIX® Arch Support System

Optimal ankle support and shock absorption in the arch provided by an anatomically formed last; good foot guidance and proper hold thanks to narrow heel and ankle shaft combined with added comfort through broad front foot area.

### HAIX® Identification System

Name field for boot labelling.

### HAIX® Vario Wide Fit System

Three different boot inserts enable you to adjust the boot to the width of your feet.

### HAIX® Climate System

Micro-dry lining around the upper end of the shaft allows moist air to be released with every step while fresh air enters the boot through the vent holes along the shaft and tongue.

### HAIX® Fast Lacing Fit System

Patented two-zone lacing system for quick and optimal lacing adjustment and correct fit of the boot. Added safety thanks to integrated instep protection.

### Sun Reflect

Reduces heating effect on the upper leather. Sunlight is reflected, keeping leather and feet cooler.

### Others

Lateral reflective strips, two-zone lacing system with patented protector, extra flexible shaft and pull-on straps, boot jack

|    |    |     |    |     |    |     |    |     |    |     |    |     |    |      |    |      |    |      |    |      |    |      |    |      |    |
|----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|------|----|------|----|------|----|------|----|------|----|------|----|
| UK | 3  | 3 ½ | 4  | 4 ½ | 5  | 5 ½ | 6  | 6 ½ | 7  | 7 ½ | 8  | 8 ½ | 9  | 9 ½  | 10 | 10 ½ | 11 | 11 ½ | 12 | 12 ½ | 13 | 13 ½ | 14 | 14 ½ | 15 |
| EU | 35 | 36  | 37 | 37  | 38 | 39  | 39 | 40  | 41 | 41  | 42 | 43  | 43 | 44   | 45 | 45   | 46 | 47   | 47 | 48   | 48 | 49   | 50 | 50   | 51 |
| US | 4  | 4 ½ | 5  | 5 ½ | 6  | 6 ½ | 7  | 7 ½ | 8  | 8 ½ | 9  | 9 ½ | 10 | 10 ½ | 11 | 11 ½ | 12 | 12 ½ | 13 | 13 ½ | 14 | 14 ½ | 15 | 15 ½ | 16 |

### HAIX®-Schuhe Produktions- und Vertriebs GmbH

Auhofstrasse 10, 84048 Mainburg, Germany  
T. +49(0)8751/8625-0, F. +49(0)8751/8625-25  
info@haix.de, www.haix.com